



R3832

Material
Stainless steel (A4).

Technical Notes
To DIN 1480.

Tips
Turnbuckles consist of a metal frame with right hand thread one end and left hand thread the other end. Used for tensioning by rotating turnbuckle body

without twisting attached rope or cable.

Important Notes
Turnbuckles are not to be used for lifting.
Only suitable for use in tension.

Order No.	d ₁	l ₁	l ₂	l ₃	d ₂	d ₃	w ₁	w ₂	Adjustment	⚖️ Kg
R3832.050-070-A4	M 5	70								
R3832.060-110-A4	M 6	110	12	6	12	6	19	9	80	0,06
R3832.060-090-A4	M 6	90	12	6	8	6	19	9	80	0,06
R3832.080-110-A4	M 8	110	15	8	15	8	23	11	75	0,09
R3832.100-125-A4	M10	125	18	9	18	9	30	14	85	0,15
R3832.100-150-A4	M10	150	18	9	16	9	30	14	85	0,15
R3832.120-125-A4	M12	125	21	11	21	11	34	16	80	0,20
R3832.120-200-A4	M12	200	21	11	18	11	34	16	80	0,20
R3832.160-170-A4	M16	170	27	14	27	14	42	20	110	0,44
R3832.160-250-A4	M16	250	27	14	26	14	42	20	110	0,44
R3832.200-200-A4	M20	200	34	17	34	17	52	24	130	0,44
R3832.200-300-A4	M20	300	34	17	30	17	52	24	130	0,44
R3832.024-255-A4	M24	255	39	20	39	20	60	28	170	1,20