

## R3631

### Material

Seal: neoprene rubber.  
Washer: stainless steel.

### Technical Notes


Washers for additional protection of bearing for use with series K rod ends. Consisting of grease, oil, saltwater, as

well as several chemicals.

Temperature range -20°C to +110°C

### Tips

Before installation, fill cup half full with waterpump grease.

Order No.	Suitable for rod end bore size	$d_1 \pm 0.13$	$d_2 \pm 0.13$	$d_3 \pm 0.25$	$w_1 \pm 0.25$	$w_2 \pm 0.13$	 g
<b>R3631.005</b>	5	5,25	8,28	11,22	2,41	0,50	1
<b>R3631.006</b>	6	6,25	9,53	12,7	3,05	0,69	1
<b>R3631.008</b>	8	8,25	12,37	17,78	5,08	1,20	2
<b>R3631.010</b>	10	10,25	13,46	20,32	5,59	1,20	2
<b>R3631.012</b>	12	12,25	18,54	28,58	6,35	1,20	3
<b>R3631.014</b>	14	14,25	20,32	29,21	6,86	1,20	3
<b>R3631.016</b>	16	16,25	22,4	31,7	6,8	1,20	4
<b>R3631.018</b>	18	18,25	22,6	32,69	8,25	1,20	5
<b>R3631.020</b>	20	20,25	25,15	38,1	10,16	1,20	6
<b>R3631.025</b>	25	25,25	33,8	53,3	12,7	1,50	9
<b>R3631.030</b>	30	30,25	35,56	55,88	19,97	1,53	11