

R3802

Material
Stainless steel (A4).

Technical Notes
To DIN 1478.

Tips


Turnbuckles consist of a metal frame with right hand thread one end and left hand thread the other end. Used for tensioning by rotating turnbuckle body

without twisting attached rope or cable.

Important Notes

Turnbuckles are not to be used for lifting.

Only suitable for use in tension.

Order No.	d ₁	l ₁	l ₂	d ₂	d _{3 min}	d _{3 max}	h	Adjustment	 Kg
R3802.006	M 6	110	7,5	17,2	5,7	6,3	2,9	90	0,13
R3802.008	M 8	110	10	17,2	7,5	8,5	3,6	85	0,13
R3802.010	M10	125	12	21,3	7,5	8,5	4,0	95	0,18
R3802.012	M12	125	15	25,0	9,5	10,5	4,0	90	0,25
R3802.016	M16	170	20	30,0	9,5	10,5	4,5	120	0,45
R3802.020	M20	200	24	33,7	11,5	12,5	5,0	140	0,56
R3802.024	M24	255	29	42,4	11,5	12,5	5,6	180	1,08
R3802.030	M30	255	36	51,0	15,5	16,5	6,3	160	1,61
R3802.036	M36	295	43	63,5	15,5	16,5	8,0	180	2,35