



Jaw End Turnbuckle

steel

Turnbuckles



R3848

Material

Steel body (1.0037), jaws (1.0503).
Zinc plated (hot dip galvanized).

Technical Notes

To DIN 1480 jaw to jaw.

Tips

Turnbuckles consist of a metal frame with right hand thread one end and left hand thread the other end. Used for tensioning by rotating turnbuckle body

without twisting attached rope or cable.

Important Notes

Turnbuckles are not to be used for lifting.

Only suitable for use in tension.

Order No.	d_1	l_1	l_2	l_3	l_4	d_2	l_5	l_6 min	l_6 max	w	$\frac{\Delta}{\Delta}$ Kg
R3848.008	M 8	110	68	116	28,75	8,5	125	250	325	9,0	0,14
R3848.010	M10	125	82	130	29,25	8,5	139	279	364	10,7	0,26
R3848.012	M12	125	90	150	44,75	10,5	160	321	401	15,5	0,40
R3848.016	M16	170	102	172	45,25	12,5	186	372	482	20,0	0,64
R3848.020	M20	200	115	185	59,50	17,5	205	410	540	23,5	1,30
R3848.024	M24	255	125	215	62,75	20,5	240	481	651	29,0	2,28
R3848.030	M30	255	150	255	89,50	25,5	290	581	741	34,0	4,02